

App. No. 09/788,301

Request for continued examination under 37 CFR §1.114

AMENDMENT TO THE SPECIFICATION

Please amend the Abstract as set forth hereinbelow.

~~The present invention applies to resonant optical power control device assemblies and methods relating thereto, and includes an An alignment device preferably including includes an alignment member with one or more waveguide-alignment grooves, resonator alignment grooves, and and/or an alignment grooves groove for a second optical element including such as a modulator. One embodiment includes a transmission optical waveguide, a circumferential mode optical resonator, and a second optical element, optionally including one or more of an optical modulator or a second transmission optical waveguide, and optionally including a modulator optical control element. In this embodiment, the The various alignment grooves reliably establish and stably maintain evanescent optical coupling between the optical elements positioned therein, in each grooves. A method for assembling a resonant optical power control devices is also disclosed. The method includes: device may include: fabricating an alignment substrate member having various with the alignment grooves; positioning and securing the various optical elements in their corresponding alignment grooves so that the resonator and the transmission optical waveguide are optically coupled (through close proximity and/or direct contact between them), and similarly optically coupling the resonator and any second optical element. for optical coupling therebetween.~~ Alignment grooves in the substrate and/or in one or more of the optical elements are fabricated at proper depths and positions and preferably with mating grooves and/or flanges to enable the optical coupling without extensive active alignment procedures. A modulator can alternatively be provided as an integral component of the resonator, directly on the resonator, or as a separate assembly positioned on and secured with respect to the alignment substrate. The modulator enables control of the resonator, which in turn controls the optical power transmitted through the transmission optical waveguide and/or the second optical element. Structures may also be provided for suppressing undesired optical modes and/or resonances associated with resonators and/or alignment structures on the optical fiber.

Faxed to 703-872-9306 on 03/24/2004

Page 2 of 74